

# Бумажные этикеточные клеевые материалы из мелованной бумаги

## Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: [has@nt-rt.ru](mailto:has@nt-rt.ru) || сайт: <https://herma.nt-rt.ru/>

| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
|--------------|-------------------------------------------|----------------|-----------|---------------|------------|--------------|
| 16889        | HERMAcoat WS (229)/62P/523                | 2,000 mm       |           | 2,000 m²      | ca. 130 µm | ca. 152 g/m² |
| 17196        | HERMAcoat WS (229)/62Rpw/523              | 2,000 mm       |           | 2,000 m²      | ca. 132 µm | ca. 153 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 14408        | HERMAsuper 60 (232)/62Gpt/523             | 1,523 mm       |           | 1,520 m²      | ca. 117 µm | ca. 134 g/m² |
| 15021        | HERMAsuper 60 (232)/63Z/525               | 1,523 mm       |           | 1,520 m²      | ca. 134 µm | ca. 159 g/m² |
| 15094        | HERMAsuper 60 (232)/63S/525 35g/m²        | 2,000 mm       |           | 2,000 m²      | ca. 149 µm | ca. 168 g/m² |
| 15462        | HERMAsuper 60 (232)/63Z/512               | 1,523 mm       |           | 7,500 m²      | ca. 146 µm | ca. 140 g/m² |
| 15475        | HERMAsuper 60 (232)/63Mps/525             | 1,523 mm       |           | 1,520 m²      | ca. 139 µm | ca. 157 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 16629        | HERMAcoat Recycling (236)/62Gpt/523       | 1,523 mm       |           | 1,520 m²      | ca. 117 µm | ca. 144 g/m² |
| 16735        | HERMAcoat Recycling (236)/62Gpo/523       | 1,523 mm       |           | 7,500 m²      | ca. 143 µm | ca. 157 g/m² |
| 17041        | HERMAcoat Recycling (236)/62D/520/62D/523 | 1,523 mm       |           | 7,500 m²      | ca. 198 µm | ca. 217 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 17558        | HERMAcoat light (238)/61Dps/560           | 2,000 mm       |           | 16,000 m²     | ca. 98 µm  | ca. 118 g/m² |
| 17553        | HERMAcoat light (238)/62D/560             | 2,000 mm       |           | 16,000 m²     | ca. 100 µm | ca. 117 g/m² |
| 17550        | HERMAcoat light (238)/71N/500             | 1,523 mm       |           | 1,500 m²      | ca. 120 µm | ca. 141 g/m² |
| 17030        | HERMAcoat light (238)/61Dps/520           |                |           | 7,500 m²      | ca. 120 µm | ca. 141 g/m² |
| 16809        | HERMAcoat light (238)/62Gpt/523           | 1,523 mm       |           | 7,500 m²      | ca. 125 µm | ca. 145 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 16505        | HERMAcoat light (238)/61Dps/543           | 1,523 mm       |           | 7,500 m²      | ca. 115 µm | ca. 131 g/m² |
| 16265        | HERMAcoat light (238)/61Dps/523           | 1,523/2,000 mm |           | 1,520 m²      | ca. 114 µm | ca. 140 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 06599        | HERMAwhite super (240)/42N/523            | 1,523 mm       |           | 7,500 m²      | ca. 119 µm | ca. 147 g/m² |
| 14224        | HERMAwhite super (240)/62Gpt/565          | 2,000 mm       |           | 2,000 m²      | ca. 104 µm | ca. 135 g/m² |
| 15247        | HERMAwhite super (240)/63Vst/523          | 1,523 mm       |           | 1,520 m²      | ca. 132 µm | ca. 162 g/m² |
| 15476        | HERMAwhite super (240)/63Mps/523          | 1,523 mm       |           | 1,520 m²      | ca. 138 µm | ca. 160 g/m² |
| 15553        | HERMAwhite super (240)/62Gpt/523          | 1,523/2,000 mm |           | 1,520 m²      | ca. 123 µm | ca. 150 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 15692        | HERMAwhite super (240)/62Gpt/560          | 2,000 mm       |           | 16,000 m²     | ca. 97 µm  | ca. 126 g/m² |
| 15853        | HERMAwhite super (240)/62D/523            | 1,523/2,000 mm |           | 1,520 m²      | ca. 122 µm | ca. 148 g/m² |
| 15859        | HERMAwhite super (240)/62D/780            | 1,523 mm       |           | 1,520 m²      | ca. 122 µm | ca. 150 g/m² |
| 15860        | HERMAwhite super (240)/62Gpt/780          | 1,523 mm       |           | 1,520 m²      | ca. 124 µm | ca. 152 g/m² |
| 15869        | HERMAwhite super (240)/65Tpc/525          | 2,000 mm       |           | 2,000 m²      | ca. 160 µm | ca. 190 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 16460        | HERMAwhite super (240)/42E/523            | 1,523 mm       |           | 7,500 m²      | ca. 114 µm | ca. 142 g/m² |
| 16627        | HERMAwhite super (240)/62Vst/523          | 1,523 mm       |           | 7,500 m²      | ca. 156 µm | ca. 156 g/m² |
| 17540        | HERMAwhite super (240)/72Bpt/523          | 1,523/2,000 mm |           | 1,520 m²      | ca. 124 µm | ca. 150 g/m² |
| 17867        | HERMAwhite super (240)/62Dps/565          | 2,000 mm       |           | 2,000 m²      | ca. 110 µm | ca. 135 g/m² |
| Product Code | Product                                   | Useable width  | Net width | Min. quantity | Caliper    | Grammage     |
| 12244        | HERMAextracoat (242)/62A/523              | 1,003 mm       |           | 1,000 m²      | ca. 129 µm | ca. 153 g/m² |
| 12245        | HERMAextracoat (242)/92C/523              | 1,003 mm       |           | 1,000 m²      | ca. 131 µm | ca. 154 g/m² |
| 12246        | HERMAextracoat (242)/62D/523              | 1,523/2,000 mm |           | 1,520 m²      | ca. 122 µm | ca. 149 g/m² |

| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
|--------------|-------------------------------------------------|----------------|-----------|-----------------------|------------|--------------------------|
| 12254        | HERMAextracoat (242)/42N/523                    | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 120 µm | ca. 146 g/m <sup>2</sup> |
| 12257        | HERMAextracoat (242)/64B/520                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 149 µm | ca. 174 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 12258        | HERMAextracoat (242)/64B/523                    | 1,003 mm       |           | 1,000 m <sup>2</sup>  | ca. 148 µm | ca. 174 g/m <sup>2</sup> |
| 12259        | HERMAextracoat (242)/63B/523                    | 1,003 mm       |           | 1,000 m <sup>2</sup>  | ca. 133 µm | ca. 158 g/m <sup>2</sup> |
| 12262        | HERMAextracoat (242)/52A/523 14g/m <sup>2</sup> | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 126 µm | ca. 148 g/m <sup>2</sup> |
| 12275        | HERMAextracoat (242)/62Dpc/527                  | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 151 µm | ca. 167 g/m <sup>2</sup> |
| 12276        | HERMAextracoat (242)/62Gpt/523                  | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 123 µm | ca. 150 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 12277        | HERMAextracoat (242)/62K/523                    | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 130 µm | ca. 151 g/m <sup>2</sup> |
| 12279        | HERMAextracoat (242)/63Z/523                    | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 135 µm | ca. 158 g/m <sup>2</sup> |
| 12281        | HERMAextracoat (242)/62D/520/62D/523            | 1,523/2,000 mm |           | 7,500 m <sup>2</sup>  | ca. 188 µm | ca. 235 g/m <sup>2</sup> |
| 12290        | HERMAextracoat (242)/62Gpt/517                  | 1,523/2,000 mm |           | 7,500 m <sup>2</sup>  | ca. 126 µm | ca. 155 g/m <sup>2</sup> |
| 12291        | HERMAextracoat (242)/62Z/523                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 133 µm | ca. 155 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 12292        | HERMAextracoat (242)/62D/520                    | 1,523/2,000 mm |           | 7,500 m <sup>2</sup>  | ca. 121 µm | ca. 149 g/m <sup>2</sup> |
| 12294        | HERMAextracoat (242)/63Gpt/523                  | 1,523/2,000 mm |           | 7,500 m <sup>2</sup>  | ca. 131 µm | ca. 158 g/m <sup>2</sup> |
| 12296        | HERMAextracoat (242)/65B/523                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 164 µm | ca. 184 g/m <sup>2</sup> |
| 12358        | HERMAextracoat (242)/62A/815/62A/523            | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 181 µm | ca. 216 g/m <sup>2</sup> |
| 12388        | HERMAextracoat (242)/62A/520/62A/523            | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 200 µm | ca. 237 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 12452        | HERMAextracoat (242)/62Gpt/520                  | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 123 µm | ca. 152 g/m <sup>2</sup> |
| 12457        | HERMAextracoat (242)/62D/525                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 137 µm | ca. 167 g/m <sup>2</sup> |
| 12483        | HERMAextracoat (242)/42N/520                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 127 µm | ca. 150 g/m <sup>2</sup> |
| 12484        | HERMAextracoat (242)/62Gpt/525                  | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 139 µm | ca. 170 g/m <sup>2</sup> |
| 12505        | HERMAextracoat (242)/62B/523                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 130 µm | ca. 155 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 12701        | HERMAextracoat (242)/92K/523                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 131 µm | ca. 154 g/m <sup>2</sup> |
| 12904        | HERMAextracoat (242)/62Gpt/527                  | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 150 µm | ca. 167 g/m <sup>2</sup> |
| 13183        | HERMAextracoat (242)/63B/523/63B/523            | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 203 µm | ca. 244 g/m <sup>2</sup> |
| 13368        | HERMAextracoat (242)/62D/520/42N/523            | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 196 µm | ca. 234 g/m <sup>2</sup> |
| 13485        | HERMAextracoat (242)/62D/517                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 124 µm | ca. 155 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 13567        | HERMAextracoat (242)/62Gpt/523/62Gpt/523        | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 191 µm | ca. 235 g/m <sup>2</sup> |
| 13617        | HERMAextracoat (242)/42N/520/62D/523            | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 191 µm | ca. 222 g/m <sup>2</sup> |
| 13686        | HERMAextracoat (242)/62Gpt/560                  | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 97 µm  | ca. 126 g/m <sup>2</sup> |
| 14033        | HERMAextracoat (242)/62D/525 BW                 | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 138 µm | ca. 165 g/m <sup>2</sup> |
| 14156        | HERMAextracoat (242)/62Dpc/511                  | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 192 µm | ca. 216 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 14411        | HERMAextracoat (242)/42Upp/523                  | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 121 µm | ca. 143 g/m <sup>2</sup> |
| 14490        | HERMAextracoat (242)/62D/560                    | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 96 µm  | ca. 124 g/m <sup>2</sup> |
| 14522        | HERMAextracoat (242)/42N/511                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 197 µm | ca. 214 g/m <sup>2</sup> |

| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
|--------------|------------------------------------------------------------|----------------|-----------|-----------------------|------------|--------------------------|
| 14641        | HERMAextracoat (242)/63B/815                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 119 µm | ca. 144 g/m <sup>2</sup> |
| 14645        | HERMAextracoat (242)/64B/525                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 161 µm | ca. 190 g/m <sup>2</sup> |
| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 14934        | HERMAextracoat (242)/62Gpt/520/62Gpt/523                   | 1,003/1,523 mm |           | 7,500 m <sup>2</sup>  | ca. 191 µm | ca. 232 g/m <sup>2</sup> |
| 14976        | HERMAextracoat (242)/42E/523                               | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 122 µm | ca. 144 g/m <sup>2</sup> |
| 14998        | HERMAextracoat (242)/63Spc/525                             | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 160 µm | ca. 187 g/m <sup>2</sup> |
| 15086        | HERMAextracoat (242)/62A/815/62A/517 18/16g/m <sup>2</sup> | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 185 µm | ca. 223 g/m <sup>2</sup> |
| 15520        | HERMAextracoat (242)/52A/527                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 152 µm | ca. 165 g/m <sup>2</sup> |
| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 15600        | HERMAextracoat (242)/41Upp/523                             | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 123 µm | ca. 144 g/m <sup>2</sup> |
| 15681        | HERMAextracoat (242)/63Vst/527                             | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 156 µm | ca. 176 g/m <sup>2</sup> |
| 15731        | HERMAextracoat (242)/63B/527                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 162 µm | ca. 175 g/m <sup>2</sup> |
| 15920        | HERMAextracoat (242)/62A/520                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 128 µm | ca. 157 g/m <sup>2</sup> |
| 15957        | HERMAextracoat (242)/62Gpo/523                             | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 132 µm | ca. 154 g/m <sup>2</sup> |
| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 15980        | HERMAextracoat (242)/42U/527                               | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 148 µm | ca. 162 g/m <sup>2</sup> |
| 16015        | HERMAextracoat (242)/93C/523 30g/m <sup>2</sup>            | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 138 µm | ca. 164 g/m <sup>2</sup> |
| 16168        | HERMAextracoat (242)/63Vst/523                             | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 139 µm | ca. 159 g/m <sup>2</sup> |
| 16176        | HERMAextracoat (242)/94C/523                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 147 µm | ca. 174 g/m <sup>2</sup> |
| 16339        | HERMAextracoat (242)/62Vst/523                             | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 127 µm | ca. 156 g/m <sup>2</sup> |
| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 16447        | HERMAextracoat (242)/42Lpp/523                             | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 127 µm | ca. 148 g/m <sup>2</sup> |
| 16510        | HERMAextracoat (242)/42X/815                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 106 µm | ca. 138 g/m <sup>2</sup> |
| 16546        | HERMAextracoat (242)/62A/C00/523/C40                       |                |           | 3,000 m <sup>2</sup>  | ca. 128 µm | ca. 154 g/m <sup>2</sup> |
| 16568        | HERMAextracoat (242)/42X/523                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 130 µm | ca. 152 g/m <sup>2</sup> |
| 16575        | HERMAextracoat (242)/62D/532 Offset                        | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 130 µm | ca. 152 g/m <sup>2</sup> |
| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 16576        | HERMAextracoat (242)/62Gpt/532 Offset                      | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 122 µm | ca. 150 g/m <sup>2</sup> |
| 16646        | HERMAextracoat (242)/42N/523 S44                           | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 127 µm | ca. 150 g/m <sup>2</sup> |
| 16723        | HERMAextracoat (242)/62Dpc/510                             | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 164 µm | ca. 189 g/m <sup>2</sup> |
| 16776        | HERMAextracoat (242)/63B/517                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 138 µm | ca. 162 g/m <sup>2</sup> |
| 16780        | HERMAextracoat (242)/62D/520/62D/520                       | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 197 µm | ca. 230 g/m <sup>2</sup> |
| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 16790        | HERMAextracoat (242)/62D/565                               | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 108 µm | ca. 134 g/m <sup>2</sup> |
| 16822        | HERMAextracoat (242)/62P/523                               | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 123 µm | ca. 150 g/m <sup>2</sup> |
| 16828        | HERMAextracoat (242)/42Lpp/527                             | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 149 µm | ca. 165 g/m <sup>2</sup> |
| 16989        | HERMAextracoat (242)/52C/523                               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 126 µm | ca. 146 g/m <sup>2</sup> |
| 17117        | HERMAextracoat (242)/63Z/560                               | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 108 µm | ca. 137 g/m <sup>2</sup> |
| Product Code | Product                                                    | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 17150        | HERMAextracoat (242)/62E/520                               | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 123 µm | ca. 143 g/m <sup>2</sup> |
| 17287        | HERMAextracoat (242)/62D/780                               | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 127 µm | ca. 153 g/m <sup>2</sup> |
| 17436        | HERMAextracoat (242)/65Tpc/565                             | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 140 µm | ca. 165 g/m <sup>2</sup> |

| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
|--------------|------------------------------------------------|----------------|-----------|-----------------------|------------|--------------------------|
| 17536        | HERMAextracoat (242)/72Bpt/523                 | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 125 µm | ca. 150 g/m <sup>2</sup> |
| 17542        | HERMAextracoat (242)/62Q/520                   | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 117 µm | ca. 143 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 17560        | HERMA extracoat duplex (242)/62Gpt/520/42N/523 |                |           | 7,500 m <sup>2</sup>  | ca. 190 µm | ca. 232 g/m <sup>2</sup> |
| 17868        | HERMAextracoat (242)/62Dps/560                 | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 104 µm | ca. 125 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 17575        | HERMAcoat (243)/62Dps/523                      | 1,523/2,000 mm |           | 2,000 m <sup>2</sup>  | ca. 127 µm | ca. 148 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 13269        | HERMAcoat opaque (244)/62Gpt/523               | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 141 µm | ca. 167 g/m <sup>2</sup> |
| 13761        | HERMAcoat opaque (244)/62Gpt/527               | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 167 µm | ca. 183 g/m <sup>2</sup> |
| 13823        | HERMAcoat opaque (244)/42N/523                 | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 135 µm | ca. 159 g/m <sup>2</sup> |
| 14205        | HERMAcoat opaque (244)/62D/523                 | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 135 µm | ca. 160 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 04120        | HERMAgloss (245)/62A/520/62A/523               | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 195 µm | ca. 235 g/m <sup>2</sup> |
| 11088        | HERMAgloss (245)/64B/523                       | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 148 µm | ca. 177 g/m <sup>2</sup> |
| 11093        | HERMAgloss (245)/63Z/523                       | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 134 µm | ca. 159 g/m <sup>2</sup> |
| 11558        | HERMAgloss (245)/62Gpt/523                     | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 132 µm | ca. 156 g/m <sup>2</sup> |
| 11627        | HERMAgloss (245)/62D/523/62D/523               | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 191 µm | ca. 231 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 11671        | HERMAgloss (245)/62D/523                       | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 122 µm | ca. 153 g/m <sup>2</sup> |
| 11672        | HERMAgloss (245)/42N/523                       | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 126 µm | ca. 153 g/m <sup>2</sup> |
| 11697        | HERMAgloss (245)/42N/527                       | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 151 µm | ca. 170 g/m <sup>2</sup> |
| 11713        | HERMAgloss (245)/62Dpc/527                     | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 149 µm | ca. 169 g/m <sup>2</sup> |
| 12030        | HERMAgloss (245)/63B/523                       | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 133 µm | ca. 161 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 12145        | HERMAgloss (245)/62Z/523                       | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 135 µm | ca. 158 g/m <sup>2</sup> |
| 12148        | HERMAgloss (245)/62A/815                       | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 108 µm | ca. 141 g/m <sup>2</sup> |
| 12698        | HERMAgloss (245)/62K/523                       | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 134 µm | ca. 156 g/m <sup>2</sup> |
| 14532        | HERMAgloss (245)/63Z/520                       | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 131 µm | ca. 162 g/m <sup>2</sup> |
| 15387        | HERMAgloss (245)/42N/520/62D/523               | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 196 µm | ca. 230 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 17091        | HERMAgloss (245)/93C/525                       | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 151 µm | ca. 183 g/m <sup>2</sup> |
| 17461        | HERMAgloss (245)/42E/523                       | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 118 µm | ca. 148 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 00293        | HERMAgloss B (246)/63Z/523                     | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 142 µm | ca. 166 g/m <sup>2</sup> |
| 00405        | HERMAgloss B (246)/62D/523                     | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 126 µm | ca. 157 g/m <sup>2</sup> |
| 06851        | HERMAgloss B (246)/62K/523                     | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 134 µm | ca. 159 g/m <sup>2</sup> |
| 08435        | HERMAgloss B (246)/42N/523                     | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 123 µm | ca. 154 g/m <sup>2</sup> |
| 09560        | HERMAgloss B (246)/92K/523                     | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 139 µm | ca. 162 g/m <sup>2</sup> |
| Product Code | Product                                        | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 12577        | HERMAgloss B (246)/62Gpt/523                   | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 138 µm | ca. 161 g/m <sup>2</sup> |

| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
|--------------|-------------------------------------------------|----------------|-----------|-----------------------|------------|--------------------------|
| 13745        | HERMAgloss B (246)/62Gpt/525                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 152 µm | ca. 178 g/m <sup>2</sup> |
| 14054        | HERMAgloss B (246)/63Gpt/523                    | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 132 µm | ca. 163 g/m <sup>2</sup> |
| 14666        | HERMAmidgloss B (246)/42N/527                   | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 159 µm | ca. 176 g/m <sup>2</sup> |
| 14687        | HERMAgloss B (246)/62W/525                      | 1,003 mm       |           | 48,000 m <sup>2</sup> | ca. 148 µm | ca. 176 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 15132        | HERMAgloss B (246)/63Gpt/527                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 165 µm | ca. 182 g/m <sup>2</sup> |
| 16064        | HERMAgloss B (246)/63Vst/523                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 143 µm | ca. 166 g/m <sup>2</sup> |
| 16895        | HERMAgloss B (246)/62B/815                      | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 119 µm | ca. 148 g/m <sup>2</sup> |
| 17587        | HERMAgloss B (246)/62Gpo/523                    | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 135 µm | ca. 158 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 14086        | HERMAgloss super (248)/62Gpt/523                | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 125 µm | ca. 152 g/m <sup>2</sup> |
| 14419        | HERMAgloss super (248)/62D/523                  | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 124 µm | ca. 152 g/m <sup>2</sup> |
| 14521        | HERMAgloss super (248)/63Z/520                  | 1,000 mm       |           | 5,000 m <sup>2</sup>  | ca. 131 µm | ca. 160 g/m <sup>2</sup> |
| 17438        | HERMAgloss super (248)/63B/525                  | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 147 µm | ca. 175 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 16800        | HERMAcoat 115 (270)/62Gpt/523                   | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 149 µm | ca. 188 g/m <sup>2</sup> |
| 17473        | HERMAcoat 115 (270)/42N/523                     | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 146 µm | ca. 184 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 11123        | HERMAwhite 170 (725)/64B/520                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 233 µm | ca. 267 g/m <sup>2</sup> |
| 11128        | HERMAwhite 170 (725)/62A/523                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 212 µm | ca. 244 g/m <sup>2</sup> |
| 11455        | HERMAwhite 170 (725)/62A/520                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 211 µm | ca. 244 g/m <sup>2</sup> |
| 12150        | HERMAwhite 170 (725)/62B/523                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 215 µm | ca. 248 g/m <sup>2</sup> |
| 12179        | HERMAwhite 170 (725)/62A/527                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 234 µm | ca. 260 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 15329        | HERMAwhite 170 (725)/52A/523 14g/m <sup>2</sup> | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 208 µm | ca. 240 g/m <sup>2</sup> |
| 15391        | HERMAwhite 170 (725)/92C/523                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 213 µm | ca. 246 g/m <sup>2</sup> |
| 15563        | HERMAwhite 170 (725)/63B/520                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 217 µm | ca. 251 g/m <sup>2</sup> |
| 15569        | HERMAwhite 170 (725)/62A/815                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 179 µm | ca. 230 g/m <sup>2</sup> |
| 16330        | HERMAwhite 170 (725)/93C/523                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 224 µm | ca. 257 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 16813        | HERMAwhite 170 (725)/94C/520                    | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 233 µm | ca. 266 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 16105        | HERMAgloss B FSC® (746)/62K/523                 | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 138 µm | ca. 162 g/m <sup>2</sup> |
| 16106        | HERMAgloss B FSC® (746)/63Vst/523               | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 143 µm | ca. 166 g/m <sup>2</sup> |
| 16414        | HERMAgloss B FSC® (746)/62D/523                 | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 137 µm | ca. 160 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 00119        | HERMApharm G (132)/63Z/525                      | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 138 µm | ca. 161 g/m <sup>2</sup> |
| 04416        | HERMApharm G (132)/63Z/515                      | 1,003 mm       |           | 5,000 m <sup>2</sup>  | ca. 119 µm | ca. 142 g/m <sup>2</sup> |
| 06372        | HERMApharm G (132)/62B/523/62A/523              | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 194 µm | ca. 219 g/m <sup>2</sup> |
| 09733        | HERMApharm G (132)/63B/815                      | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 111 µm | ca. 129 g/m <sup>2</sup> |
| 12466        | HERMApharm G (132)/62A/525                      | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 130 µm | ca. 153 g/m <sup>2</sup> |
| Product Code | Product                                         | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |

| Product Code | Product                          | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
|--------------|----------------------------------|----------------|-----------|-----------------------|------------|--------------------------|
| 15990        | HERMApharm G (132)/62A/815       | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 97 µm  | ca. 122 g/m <sup>2</sup> |
| 16041        | HERMApharm G (132)/62B/815       | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 105 µm | ca. 125 g/m <sup>2</sup> |
| 16773        | HERMApharm G (132)/63Z/565       | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 106 µm | ca. 132 g/m <sup>2</sup> |
| Product Code | Product                          | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 13815        | HERMAtransfer (226)/62Gpt/523    | 1,003 mm       |           | 24,000 m <sup>2</sup> | ca. 135 µm | ca. 149 g/m <sup>2</sup> |
| 14127        | HERMAtransfer (226)/64B/523      | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 156 µm | ca. 170 g/m <sup>2</sup> |
| 14228        | HERMAtransfer (226)/42N/523      | 1,003 mm       |           | 7,500 m <sup>2</sup>  | ca. 129 µm | ca. 145 g/m <sup>2</sup> |
| 17114        | HERMAtransfer (226)/62D/523      | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 131 µm | ca. 148 g/m <sup>2</sup> |
| Product Code | Product                          | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 11331        | HERMALux (261)/62A/815           | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 128 µm | ca. 142 g/m <sup>2</sup> |
| 16207        | HERMALux (261)/62D/523           | 1,523/2,000 mm |           | 1,520 m <sup>2</sup>  | ca. 136 µm | ca. 153 g/m <sup>2</sup> |
| 16648        | HERMALux (261)/62D/522 RSD HERMA | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 138 µm | ca. 156 g/m <sup>2</sup> |
| 16670        | HERMALux (261)/62Gpt/523         | 2,000 mm       |           | 2,000 m <sup>2</sup>  | ca. 144 µm | ca. 153 g/m <sup>2</sup> |
| 16674        | HERMALux (261)/63B/523           | 1,003 mm       |           | 1,000 m <sup>2</sup>  | ca. 154 µm | ca. 162 g/m <sup>2</sup> |
| Product Code | Product                          | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 16703        | HERMALux (261)/62Dpc/512         | 1,523 mm       |           | 1,520 m <sup>2</sup>  | ca. 153 µm | ca. 153 g/m <sup>2</sup> |
| 16716        | HERMALux (261)/62W/525           | 1,003 mm       |           | 1,000 m <sup>2</sup>  | ca. 158 µm | ca. 169 g/m <sup>2</sup> |
| 16737        | HERMALux (261)/62A/520/62A/523   | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 203 µm | ca. 233 g/m <sup>2</sup> |
| 16843        | HERMALux (261)/64B/523           | 1,003 mm       |           | 3,000 m <sup>2</sup>  | ca. 167 µm | ca. 175 g/m <sup>2</sup> |
| 16922        | HERMALux (261)/42N/523           | 1,523 mm       |           | 7,500 m <sup>2</sup>  | ca. 143 µm | ca. 151 g/m <sup>2</sup> |
| Product Code | Product                          | Useable width  | Net width | Min. quantity         | Caliper    | Grammage                 |
| 17027        | HERMALux (261)/62Gpt/565         | 2,000 mm       |           | 16,000 m <sup>2</sup> | ca. 127 µm | ca. 139 g/m <sup>2</sup> |


## Product information

**HERMAcoat 115 (270)****Product code 51806**

Issue 12/2022

**HERMAcoat 115 (270)**

White label paper, semi gloss coated, FSC® Mix Credit




|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 115 | ISO 536   |
| Caliper               | µm               | approx. 86  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 95  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 40  | DIN 53112 |
| Opacity               | %                | approx. 93  | ISO 2471  |

**Application and use**

The semi gloss coated surface of HERMAcoat 115 (270) offers an excellent quality of the imprint with all conventional printing methods.

HERMAcoat 115 (270) is particularly suitable for stiff labels. Due to the relatively high stiffness of the material, it should not be used on curved surfaces.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.

 HERMAcoat 115 (270)**Regulations concerning contact with food**


The paper complies with BfR XXXVI recommendations for direct contact with dry food.

## Product information

### HERMAcoat WS (229)

Product code 51805


Issue 06/2024



 HERMAcoat WS (229)

### HERMAcoat WS (229)

White label paper, semi-gloss coated on one side, medium wet strength



|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 80  | ISO 536   |
| Caliper               | µm               | approx. 66  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 65  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 40  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 135 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 90  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 18  | ISO 2813  |
| Opacity               | %                | approx. 86  | ISO 2471  |

### Application and use

HERMAcoat WS (229) is perfect for high-quality labels with multi-colour imprint. The semi-gloss coated surface offers an excellent quality of the imprint with all conventional printing methods and good printing quality with thermal transfer and laser printing. Furthermore HERMAcoat WS is printable with digital printing methods. Pre-testing is recommended. Thanks to its medium wet-strength HERMAcoat WS is well suited for wash-off applications.


### Regulations concerning contact with food

The paper complies with BfR XXXVI recommendations for direct contact with dry and fatty food.


## Product information

**HERMAcoat Recycling (236)****Product code 51580**

Issue 04/2024

 **HERMAcoat Recycling (236)****HERMAcoat Recycling (236)**

Natural white label paper, semi-gloss coated on one side, made from 100 % recycled fibre, FSC recycled



|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 70  | ISO 536   |
| Caliper               | µm               | approx. 73  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 45  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 23  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 110 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 55  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 10  | ISO 2813  |
| Opacity               | %                | approx. 97  | ISO 2471  |

**Application and use**

HERMAcoat recycling with 100 % recycled fibre is a sustainable and versatile label paper for multicolour printing. The natural white, semi-gloss coated surface of HERMAcoat recycling offers good print quality with all conventional printing methods. Thermal transfer printing is also possible, pre-testing is recommended. Due to the recycled fiber the paper has low tensile strength, which is why the production speed should not be too high.


The ecological advantage of recycled paper is mainly due to the significantly reduced water and energy requirements in fibre preparation and the elimination of long transport routes for primary fibres.

The face paper has the "Blue Angel" ecolabel.


## Product information

**HERMAcoat (243)****Product code 51521**

Issue 03/2023

 HERMAcoat (243)**HERMAcoat (243)**

White label paper, semi-gloss coated on one side,  
FSC® Mix Credit



|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 77  | ISO 536   |
| Caliper               | µm               | approx. 65  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 65  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 35  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 140 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 85  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 27  | ISO 2813  |
| Opacity               | %                | approx. 85  | ISO 2471  |

**Application and use**

The semi-gloss coated surface of HERMAcoat (243) offers an excellent quality of the imprint with all traditional printing methods. HERMAcoat (243) is perfect for high-quality labels with multi-colour imprint as well as for thermal transfer and laser printing. It is also suitable for digital printing methods like HP Indigo, Xeikon and UV-Inkjet. Pre-testing is recommended.

The pulp for this paper is from FSC® certified forests and other controlled sources.

**Regulations concerning contact with food**

The paper complies with BfR XXXVI recommendations for direct contact with dry and fatty food.

## Product information


### HERMAcoat light (238)

Product code 51332

Issue 12/2022

#### HERMAcoat light (238)


White label paper, semi-gloss coated on one side, FSC® Mix Credit



|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 70  | ISO 536   |
| Caliper               | µm               | approx. 60  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 65  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 34  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 100 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 50  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 20  | ISO 2813  |
| Opacity               | %                | approx. 82  | ISO 2471  |

#### Application and use

HERMAcoat light is suitable for high-quality labels with multi-colour imprint. The semi-gloss coated surface of HERMAcoat light offers an excellent quality of the imprint with all conventional printing methods as well as with thermal transfer and laser printing. Furthermore HERMAcoat light is suitable for digital printing methods Xeikon and UV-Inkjet. Pre-testing is recommended. The pulp for this paper comes from FSC® certified forest management and other controlled sources.



HERMAcoat light (238)


#### Regulations concerning contact with food

The paper complies with BfR XXXVI recommendations for direct contact with dry and non fatty food.

## Product information

**HERMAgloss B FSC® (746)****Product code 50083**

Issue 12/2022

**HERMAgloss B FSC® (746)**White label paper, glossy coated on one side,  
FSC® Mix Credit


|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 85  | ISO 536   |
| Caliper               | µm               | approx. 70  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 70  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 35  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 200 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 100 | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 38  | ISO 2813  |
| Opacity               | %                | approx. 86  | ISO 2471  |

**Application and use**

The glossy surface of the HERMAgloss B FSC® offers an excellent quality of the imprint with all conventional methods.

HERMAgloss B FSC® is used for high-quality labels with elaborate printing, such as decoration, advertising and product labels.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.


 **HERMAgloss B FSC®  
(746)****Regulations concerning contact with food**

The paper complies with BfR XXXVI recommendations for direct contact with dry and non fatty food.

## Product information

**HERMALux (261)****Product code 50045**

Issue 12/2022

**HERMALux (261)**White high gloss paper, cast-coated on one side,  
FSC® Mix Credit


|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 78  | ISO 536   |
| Caliper               | µm               | approx. 78  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 60  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 33  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 200 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 100 | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 50  | ISO 2813  |
| Opacity               | %                | approx. 88  | ISO 2471  |

**Application and use**

The cast-coated high gloss surface of HERMALux offers a perfect printing quality in all conventional printing processes. Tests with the applied printing inks are recommended. HERMALux is also suitable for thermal transfer printing. Resin tapes are recommended.

HERMALux is particularly suitable for high-quality labels with especially demanding multicolour printing.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.

 **HERMALux (261)****Regulations concerning contact with food**


This paper is approved according to the BfR Recommendation XXXVI. It may stand in direct contact with dry and non-fatty foodstuffs.

## Product information

### HERMAgloss super (248)

Product code 50040


Issue 12/2022



 HERMAgloss super (248)

### HERMAgloss super (248)

White label paper, glossy coated on one side, with high surface gloss



|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 78  | ISO 536   |
| Caliper               | µm               | approx. 66  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 60  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 40  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 130 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 85  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 60  | ISO 2813  |
| Opacity               | %                | approx. 86  | ISO 2471  |

### Application and use

The high surface gloss of HERMAgloss super offers an excellent quality of the imprint with all conventional printing methods. HERMAgloss super is used for high-quality labels with elaborate imprint, such as ornamental, advertising and product labels.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.


### Regulations concerning contact with food

The paper complies with BfR XXXVI recommendations for direct contact with dry and/or fatty food.

## Product information

**HERMAgloss (245)****Product code 50038**

Issue 12/2022


**HERMAgloss (245)**White label paper, glossy coated on one side,  
FSC® Mix Credit

|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 80  | ISO 536   |
| Caliper               | µm               | approx. 65  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 70  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 35  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 150 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 80  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 50  | ISO 2813  |
| Opacity               | %                | approx. 86  | ISO 2471  |

**Application and use**

The glossy surface of the HERMAgloss offers an excellent quality of the imprint with all conventional printing methods. HERMAgloss is used for high-quality labels with pretentious printing, such as ornamental, advertising and product labels.

The pulp for this paper comes from FSC certified forest management and other controlled sources.


 HERMAgloss (245)**Regulations concerning contact with food**

The paper complies with BfR XXXVI recommendations for direct contact with dry and non fatty food.


## Product information

**HERMAcoat opaque (244)****Product code 50037**

Issue 12/2022

 HERMAcoat opaque (244)**HERMAcoat opaque (244)**

White label paper, semi-gloss coated on one side with an opaque reverse side coating for higher opacity, FSC® Mix Credit



|                       |                  |              |           |
|-----------------------|------------------|--------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 90   | ISO 536   |
| Caliper               | µm               | approx. 75   | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 75   | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 36   | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 210  | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 100  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 15   | ISO 2813  |
| Opacity               | %                | approx. 99.7 | ISO 2471  |

**Application and use**


The semi-gloss coated surface of HERMAcoat opaque offers an excellent print quality in all conventional printing methods as well as in thermal transfer printing. Due to its total opacity the label material obscures the labelled surface completely.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.

## Product information

**HERMAwhite super (240)****Product code 50036**

Issue 10/2023

**HERMAwhite super (240)**White label paper, semi-gloss coated on one side,  
FSC® Mix Credit


|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 77  | ISO 536   |
| Caliper               | µm               | approx. 64  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 65  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 35  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 160 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 90  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 23  | ISO 2813  |
| Opacity               | %                | approx. 88  | ISO 2471  |

**Application and use**

HERMAwhite super is perfect for high-quality labels with multi-colour imprint. The semigloss coated surface offers an excellent quality of the imprint with all conventional printing methods as well as with thermal transfer and laser printing.

Furthermore is HERMAextracoat (240) printable digital printing methods. Pretesting is recommended.

The pulp for this paper is from FSC® certified forests and other controlled sources.

 HERMAwhite super (240)**Regulations concerning contact with food**


The paper complies with BfR XXXVI recommendations for direct contact with dry and fatty food.

## Product information

### HERMAsuper 60 (232)

Product code 50035


Issue 04/2023



 HERMAsuper 60 (232)

### HERMAsuper 60 (232)

White label paper, semi-gloss coated on one side, FSC®-Mix Credit



|                       |                  |            |           |
|-----------------------|------------------|------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 60 | ISO 536   |
| Caliper               | µm               | approx. 52 | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 60 | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 25 | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 60 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 30 | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 22 | ISO 2813  |
| Opacity               | %                | approx. 80 | ISO 2471  |

### Application and use

The semi-gloss coated surface of HERMAsuper 60 offers an excellent quality of the imprint with all conventional printing methods. The material is suited for high-quality labels with multi-colour imprint as well as for thermal transfer printing.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.

### Regulations concerning contact with food

The paper complies with BfR XXXVI recommendations for direct contact with dry and non-fatty food.


## Product information

**HERMAtransfer (226)****Product code 50033**

Issue 12/2022

**HERMAtransfer (226)**

White, matt coated speciality paper for thermal transfer printing, FSC® Mix Credit




|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 73  | ISO 536   |
| Caliper               | µm               | approx. 70  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 56  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 40  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 110 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 80  | DIN 53121 |
| Surface gloss 85°     | GU               | approx. 43  | ISO 2813  |
| Opacity               | %                | approx. 83  | ISO 2471  |

**Application and use**

The extra matt and smooth surface of HERMAtransfer offers excellent keying of the thermal transfer imprint. Optimal printing results are being achieved even with high speed prints, due to authentic reproduction and high resolution of the print image. HERMAtransfer also offers a good quality of imprint with letterpress and flexography.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.


 HERMAtransfer (226)**Regulations concerning contact with food**

The paper is not recommended for direct contact with food.

## Product information

**HERMAgloss B (246)****Product code 50011**

Issue 04/2023

**HERMAgloss B (246)**White label paper, glossy coated on one side,  
FSC® Mix Credit


|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 85  | ISO 536   |
| Caliper               | µm               | approx. 70  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 70  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 35  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 200 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 100 | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 38  | ISO 2813  |
| Opacity               | %                | approx. 88  | ISO 2471  |

**Application and use**

The glossy surface of the HERMAgloss B offers an excellent quality of the imprint with all conventional printing methods.

HERMAgloss B is used for high-quality labels with elaborate printing, such as decoration, advertising and product labels.


The pulp for this paper comes from FSC® certified forest management and other controlled sources.

 HERMAgloss B (246)**Regulations concerning contact with food**


The paper complies with BfR XXXVI recommendations for direct contact with dry and non fatty food.

**HERMAwhite 170 (725)****Product code 50006**

Issue 12/2022

 HERMAwhite 170 (725)**HERMAwhite 170 (725)**

White calendered semi-cardboard with optical brightening agents



|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 170 | ISO 536   |
| Caliper               | µm               | approx. 145 | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 110 | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 40  | DIN 53112 |
| Opacity               | %                | approx. 97  | ISO 2471  |

**Application and use**

The calendered surface of HERMAwhite 170 offers a good quality of the imprint with all conventional printing methods.

HERMAwhite 170 is particularly suitable for thick and stiff specialty labels such as ring labels. With its relatively high stiffness, this material should not be used on curved surfaces.

**Regulations concerning contact with food**

The cardboard complies with the legal requirements of the European Regulation (EC) No 1935/2004 as well as with §§ 30, 31 LFGB and BfR Recommendation XXXVI provided that the material is only used in direct contact with dry, non-fatty foodstuffs.

The verification of suitability for the intended purpose and risk management measures are subject to the one who puts the final product into circulation.

## Product information


### HERMAextracoat (242)

Product code 50004

Issue 12/2022

### HERMAextracoat (242)

White label paper, semi-gloss coated on one side, FSC® Mix Credit




|                       |                  |             |           |
|-----------------------|------------------|-------------|-----------|
| Grammage              | g/m <sup>2</sup> | approx. 77  | ISO 536   |
| Caliper               | µm               | approx. 65  | ISO 534   |
| Tensile strength (MD) | N/15 mm          | approx. 75  | DIN 53112 |
| Tensile strength (CD) | N/15 mm          | approx. 38  | DIN 53112 |
| Stiffness (MD)        | mN               | approx. 140 | DIN 53121 |
| Stiffness (CD)        | mN               | approx. 75  | DIN 53121 |
| Surface gloss 60°     | GU               | approx. 23  | ISO 2813  |
| Opacity               | %                | approx. 87  | ISO 2471  |

### Application and use

HERMAextracoat is suitable for high-quality labels with multi-colour imprint. The semi-gloss coated surface of HERMAextracoat offers an excellent quality of the imprint with all conventional printing methods as well as with thermal transfer and laser printing. Furthermore HERMAextracoat (242) can be printed with digital printing methods such as Xeikon and UV-Inkjet. Pre-testing is recommended.

The pulp for this paper comes from FSC certified forest management and other controlled sources.



HERMAextracoat (242)


### Regulations concerning contact with food

The paper complies with BfR XXXVI recommendations for direct contact with dry and non fatty food.

## Product information

### HERMApharm G (132)

Product code 50002




HERMApharm G (132)

Issue 12/2022

### HERMApharm G (132)

White label paper, semi-gloss coated on one side, particularly designed for pharmaceutical applications, FSC® Mix Credit



|                       |                  |            |            |
|-----------------------|------------------|------------|------------|
| Grammage              | g/m <sup>2</sup> | approx. 62 | ISO 536    |
| Caliper               | µm               | approx. 57 | ISO 534    |
| Tensile strength (MD) | N/15 mm          | approx. 52 | DIN 53112  |
| Tensile strength (CD) | N/15 mm          | approx. 32 | DIN 53112  |
| Stiffness (MD)        | mN               | approx. 80 | DIN 53121  |
| Stiffness (CD)        | mN               | approx. 50 | DIN 53121  |
| Surface gloss 60°     | GU               | approx. 30 | ISO 2813   |
| Opacity               | %                | approx. 85 | ISO 2471   |
| Whiteness Ciba-Geigy  | --               | approx. 8  | Ciba Geigy |

### Application and use

The semi-gloss coated surface of HERMApharm G offers an excellent quality of the imprint with all conventional printing methods.

Thanks to its high degree of suppleness HERMApharm G is eminently suitable for labelling circular items such as ampoules.

The high opacity of this label paper ensures a good coverage.

The pulp for this paper comes from FSC® certified forest management and other controlled sources.

### Regulations concerning contact with food

The paper complies with BfR XXXVI recommendations for direct contact with dry and/or greasy food.



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижегород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: [has@nt-rt.ru](mailto:has@nt-rt.ru) || сайт: <https://herma.nt-rt.ru/>